

BODMER-GEWINDE

Gewinde für optische und feinmechanische Instrumente

Durchmesser außen mm	Durchmesser Kernloch mm	Steigung mm	Gangzahl auf 25 mm
3,0	2,107	0,625	40
3,5	2,607	0,625	40
4,0	2,978	0,715	35
4,5	3,478	0,715	35
5,0	3,808	0,834	30
5,5	4,308	0,834	30
6,0	4,808	0,834	30
7,0	5,570	1,000	25
8,0	6,670	1,000	25
9,0	7,213	1,250	20
10,0	8,213	1,250	20
11,0	9,213	1,250	20
12,0	9,897	1,471	17
13,0	10,897	1,471	17
14,0	11,535	1,724	14,5
15,0	12,535	1,724	14,5
16,0	13,141	2,000	12,5
18,0	15,141	2,000	12,5
20,0	16,426	2,500	10
22,0	18,426	2,500	10
24,0	20,026	2,780	9
26,0	22,026	2,780	9
28,0	23,532	3,125	8
30,0	25,532	3,125	8
32,0	26,895	3,571	7
34,0	28,895	3,571	7
38,0	32,043	4,167	6
42,0	36,043	4,167	6
46,0	38,852	5,000	5
50,0	42,852	5,000	5

