

SÄGENGEWINDE DIN 513

Gewinde- Nenndurchmesser	Steigung mm	Durchmesser Bolzen mm	Durchmesser Kernloch Mutter mm
S 10 x 2	2,0	6,528	7,000
S 12 x 3	3,0	6,794	7,500
S 14 x 3	3,0	8,794	9,500
S 16 x 4	4,0	9,058	10,000
S 18 x 4	4,0	11,058	12,000
S 20 x 4	4,0	13,058	14,000
S 22 x 5	5,0	13,322	14,500
S 24 x 5	5,0	15,322	16,500
S 26 x 5	5,0	17,322	18,500
S 28 x 5	5,0	19,322	20,500
S 30 x 6	6,0	19,586	21,000
S 32 x 6	6,0	21,586	23,000
S 34 x 6	6,0	23,586	25,000
S 36 x 6	6,0	25,586	27,000
S 38 x 7	7,0	25,852	27,500
S 40 x 7	7,0	27,825	29,500
S 42 x 7	7,0	39,825	31,500
S 44 x 7	7,0	31,825	33,500
S 46 x 8	8,0	32,116	34,000
S 48 x 8	8,0	34,116	36,000
S 50 x 8	8,0	36,116	38,000
S 52 x 8	8,0	38,116	40,000
S 55 x 9	9,0	39,380	41,500
S 60 x 9	9,0	44,380	46,500
S 65 x 10	10,0	47,644	50,000
S 70 x 10	10,0	52,644	55,000
S 75 x 10	10,0	57,644	60,000
S 80 x 10	10,0	62,644	65,000
S 85 x 12	12,0	64,174	67,000
S 90 x 12	12,0	69,174	72,000
S 95 x 12	12,0	74,174	77,000
S 100 x 12	12,0	79,174	82,000

