

SÄGENGEWINDE fein DIN 513

Gewinde- Nenn Durchmesser	Steigung mm	Kerndurchmesser Bolzen mm	Durchmesser Kernloch Mutter mm
S 12 x 2	2,0	8,528	9,000
S 14 x 2	2,0	10,528	11,000
S 16 x 2	2,0	12,528	13,000
S 18 x 2	2,0	14,528	15,000
S 20 x 2	2,0	16,53	17,000
S 22 x 3	3,0	16,794	17,500
S 24 x 3	3,0	18,794	19,500
S 26 x 3	3,0	20,794	21,500
S 28 x 3	3,0	22,794	23,500
S 30 x 3	3,0	24,794	25,500
S 32 x 3	3,0	26,794	27,500
S 34 x 3	3,0	28,794	29,500
S 36 x 3	3,0	30,794	31,500
S 38 x 3	3,0	32,794	33,500
S 40 x 3	3,0	34,794	35,500
S 42 x 3	3,0	36,794	37,500
S 44 x 3	3,0	38,794	39,500
S 46 x 3	3,0	40,794	41,500
S 48 x 3	3,0	42,794	43,500
S 50 x 3	3,0	44,794	39,500
S 52 x 3	3,0	46,794	47,500
S 55 x 3	3,0	49,794	50,500
S 60 x 3	3,0	54,794	55,500
S 65 x 4	4,0	58,058	59,000
S 70 x 4	4,0	63,058	64,000
S 75 x 4	4,0	68,058	69,000
S 80 x 4	4,0	73,058	74,00
S 85 x 4	4,0	78,058	79,000
S 90 x 4	4,0	83,058	84,000
S 95 x 4	4,0	88,058	89,000
S 100 x 4	4,0	93,058	94,000

